

Design by application through texture, colour and light to transform plain walls into a durable & decorative finish.

PRODUCT DESCRIPTION

PC: 88200 DATE OF ISSUE: 2019.12.09 VER 1

PlasterTEX Polished stucco is suitable for both traditional and contemporary interior walls. Once set, the plaster is hard as stone, making it a long-lasting product that requires minimal upkeep. It is used to create an elegant, smooth finish with the illusion of depth and texture.

APPLICATION of POLISHED STUCCO

PREPARATION

Ensure the surface flat and smooth with no abrasions. Use a fine filler to repair any blemishes and sand where necessary. This step is vital, as polished stucco is very thin and any imperfections in the wall will show through.

APPLICATION

Apply 1 even coat of PlasterTEX Smooth Acrylic Primer to achieve complete obliteration of the surface. Spread rate 5-7m²/litre. Allow to dry for about 4 hours. Porous surfaces may require a 2nd coat.

Use a stainless steel trowel (the smaller the better for stucco) to apply the PlasterTEX POLISHED STUCCO.

Ensure the whole area gets an even coating of stucco [± 1.0 mm thickness]

Allow to dry for 12-16 hours.

Give a very light sand using high grade paper about 400 grit.

This is very quick - an area of one square metre should take 10 seconds.

The use a stainless steel trowel or spackle tool (smaller the better for stucco) to apply the stucco in one direction and then in the other direction, making sure to overlap.

Bear in mind now the patterns you put in with trowel will come through and give the coating finish some character. Allow to dry for 12-16 hours.

Give a very light sand using high grade paper 600 grit.

Wipe the surface with a slightly water-dampened rag to remove any plaster dust.

Use the flat side of a clean steel trowel or spatula to rub the finish for a polished appearance

If required a PROTECTIVE GLAZE may be applied. Apply 1 to 2 coats of PlasterTex Multipurpose Clear Glaze.

TECHNICAL DATA

SUPPLY & PACKAGING	Ready to use. 8 kg & 32 kg containers
SPREAD RATE	1.5kg/m ² depending on the required finish.
STORAGE	Store unopened in cool conditions for up to 6-8 months. Avoid excessive heat or cold.
CLEANING TYPE & DISPOSAL	Remove as much product from the application equipment and wash with water directly after use.

	<p>Do not allow wash water to enter sewerage drains, storm water drains or water courses.</p> <p>Ensure that all wash water is collected and disposed of according to your local authority's waste regulations. Please recycle the container or responsibly dispose of it.</p>
TRANSPORT	<p>The product is non-hazardous in accordance to Transportation and Dangerous Goods Act 1996.</p>
SAFETY	<p>Non Flammable.</p> <p>Keep out of reach of children and animals.</p> <p>Ensure good ventilation during application.</p> <p>Always wear a suitable dust mask and goggles when preparing surfaces,</p> <p>Avoid accidental contact with eyes, rinse immediately with plenty of water and seek medical advice.</p> <p>Avoid accidental contact with skin, wash immediately with soap and water.</p> <p>Harmful if swallowed, seek medical attention and do not induce vomiting.</p> <p>For detailed safety information refer to Material Safety Data sheet.</p>

DISCLAIMER

All information contained herein is given in good faith based on our experience and is meant as a guide to the client. No guarantee is implied by these recommendations since conditions on site and application is beyond our control. PlasterTEX cannot be held liable if the product fails due to improper surface preparation or application. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the user's responsibility to confirm the currency of product data sheets.